

## Anti Skid Surfacing - Product Selector

		PROCALM	PROTRACK	PROGRIP	ROCBINDA
<b>Material Type</b>		Hot	Hot	Hot	Cold
<b>Clause 924 Compliance</b>		No	No	Yes	Yes
<b>BBA/HAPAS Approved</b>		No	No	Type 1	Type 1
<b>Traffic Volume</b>		Medium	Low	Medium	High
<b>Material Thickness</b>		3 - 5 mm	2 - 3 mm	3 - 5 mm	3 mm
<b>Aggregate PSV</b>		60	65	70	70
<b>Skid Resistance Value SRV</b>		65	70	70	75
<b>Application Season</b>		All year	All year	All year	April - Sept.
<b>Application Temperature</b>		> 0°C	> 0°C	> 0°C	5 - 35 °C
<b>Application Restrictions</b>		None	None	None	1 Month **
<b>Binder</b>		Coloured	Coloured	Clear	Clear
<b>Aggregate Type</b>		Granite	Granite	Bauxite	Bauxite
<b>Product Colour</b>	Buff			√	√
	Grey			√	√
	Red	√	√		√
	Green	√	√		√
	Blue				√
	Black				√
	White				√
	Others				√
<b>Surface Type</b>	Min. Condition	Average	Average	Good	Good
	Hot Rolled Asphalt	√	√	√	√
	Blacktop	√	√	√	√
	Surface Dressing	√	√	√	<b>X</b>
	Thin Layer	√	√	√	Sealing Grit
	Concrete	Primer	Primer	Primer	Primer

\*\* **Note:** Rocbinda should not be applied to new surfaces until 1 month has elapsed. This allows the oils and residues to be removed due to the early life trafficking of the pavement.